

RAVEN EYE CUSTOM

SMITH AND WESSON MP15-22[©] 10 TO 25 ROUND MAGAZINE MODIFICATION

NOTE: Check local laws before performing this modification.

Laws vary across our great nation, and it is your responsibility as the owner of the magazines to abide by these requirements.

Only proceed if you are legally allowed to perform this modification. Be safe and understand the law!

READ PRIOR TO INSTALLATION

MAKE SURE YOUR FIREARM IS UNLOADED BEFORE DOING ANY WORK ON IT.

As the end user and installer of this product, you must accept full responsibility for the correct installation of this product and the resulting condition of your firearm. If you are unwilling to accept this, return the product to the address listed below for a full refund. If you are unable to install this product, seek the services of a qualified gunsmith, or send us an email to the address listed below and we can assist you.

Step 1 Use the supplied MP15-22 loading tool key to depress the button on the floor plate.
(Note - if you purchased only the loading buttons, the kit does not contain the loading key or cap)



Step 2 Carefully slide out the floor plate. Keep tension on the spring until the spring can be safely removed. Otherwise it will cause an unsafe condition and eject out.



Step 3 The follower is limited in its range of motion by a small pin that is visible from the bottom. Use a flat head screwdriver with a minimum 6" shaft, thin works best, and firmly but in a controlled manner knock the pin out.



Step 4 Lower the follower (blue piece) to the bottom of the magazine and slide in the Raven Eye Custom loading button. Re-assemble the magazine by following steps 1-3 in reverse. Cycle the follower up and down several times to smooth out any roughness near where the pin was.



BE SAFE!

RAVEN EYE CUSTOM

www.RavenEyeCustom.com
P.O. BOX 150083 LAKEWOOD COLORADO 80215

info@raveneyecustom.com

Copyright 2013
Revised September 16, 2013

